



N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Advanced trench cell design

1.2 Applications

- ☒ MB and NB
- ☒ Half – bridge Drivers
- ☒ Motor drivers

1.3 Quick reference

- ☒ $BV \leq 100\text{ V}$
- ☒ $P_{\text{tot}} \leq 20.8\text{ W}$
- ☒ $I_D \leq 9\text{ A}$
- ☒ $R_{\text{DS(ON)}} \leq 125\text{ m}\Omega @ V_{\text{GS}} = 10\text{ V}$
- ☒ $R_{\text{DS(ON)}} \leq 135\text{ m}\Omega @ V_{\text{GS}} = 4.5\text{ V}$

Pin Description

Pin	Description	Simplified Outline	Symbol
1	Source(S1)	Top View PDFN3.3x3.3-8L	
2	Gate(G1)		
3	Source(S2)		
4	Gate(G2)		
5,6	Drain(D2)		
7,8	Drain(D1)		



2. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	100	-	V
V_{GS}	Gate-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	-	± 20	V
I_D^*	Drain Current	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	9	A
I_{DM}^{***}	Pulsed Source Current	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	36	A
P_{tot}^*	Total Power Dissipation	$T_C = 25\text{ }^{\circ}\text{C}$	-	20.8	W
T_{stg}	Storage Temperature		- 55	150	$^{\circ}\text{C}$
T_J	Junction Temperature		-	150	$^{\circ}\text{C}$
I_S	Diode Forward Current	$T_C = 25\text{ }^{\circ}\text{C}$	-	9	A
$R_{\theta JA}^*$	Thermal Resistance- Junction to Ambient		-	62.5	$^{\circ}\text{C} / \text{W}$
$R_{\theta JC}^*$	Thermal Resistance- Junction to Case		-	6	

Notes :

* Surface Mounted on 1 in² pad area, $t \leq 10\text{ sec}$

** Pulse width $\leq 10\text{ }\mu\text{s}$, duty cycle $\leq 1\%$

*** limited by bonding wire

4. Marking Information

Product Name	Marking
iM1631	iM1631 XXXXXX X : Date Code

5. Ordering Code

iM1631 □ → Assembly Material	Assembly Material G: Halogen and Lead Free Device
------------------------------	--

Note: inergy defines “ Green ” as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)



6. Electrical Characteristics (T_A = 25 °C Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _D = 250 μA	100	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = 250 μA	1.0	-	2.5	V
I _{DSS}	Zero Gate Voltage Source Current	V _{DS} = 80, V _{GS} = 0 V	-	-	1	μA
		T _J = 85 °C	-	-	30	μA
I _{GSS}	Gate Leakage Current	V _{GS} = ± 20 V, V _{DS} = 0 V	-	-	± 100	nA
R _{DS(ON)} ^a	Drain-Source On-State Resistance	V _{GS} = 10 V, I _D = 3A	-	100	125	mΩ
		V _{GS} = 4.5 V, I _D = 2A	-	105	135	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} = 3 A, V _{GS} = 0 V	-	0.8	1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} = 3 A, dI _{SD} /dt = 100 A/μs	-	35	-	nS
Q _{rr}	Reverse Recovery Charge		-	19	-	nC
Dynamic Characteristics ^b						
C _{iss}	Input Capacitance	V _{GS} = 0 V, V _{DS} = 50 V Frequency = 1 MHz	-	1006	-	pF
C _{oss}	Output Capacitance		-	26	-	
C _{rss}	Reverse Transfer Capacitance		-	24	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} = 50 V, V _{GEN} = 10 V, R _G = 4.5 Ω, R _L = 16.6Ω, I _D = 3 A	-	3.6	-	nS
t _r	Turn-on Rise Time		-	17.6	-	
t _{d(off)}	Turn-off Delay Time		-	14	-	
t _f	Turn-off Fall Time		-	19	-	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{GS} = 10 V, V _{DS} = 50 V, I _{DS} = 3 A	-	18.8	-	nC
Q _{gs}	Gate-Source Charge		-	4.2	-	
Q _{gd}	Gate-Drain Charge		-	2.6	-	

Notes :

a : Pulse test ; pulse width ≤ 300 μs, duty cycle ≤ 2 %


b : Guaranteed by design, not subject to production testing




iM1631

7. Typical Characteristics (Cont.)


Power Capability




Current Capability



Safe Operation Area




Transient Thermal Impedance






7. Typical Characteristics (Cont.)


Output Characteristics




On Resistance



Transfer Characteristics



Normalized Threshold Voltage







iM1631

7. Typical Characteristics (Cont.)


Normalized On Resistance




Diode Forward Current



Capacitance




Gate Charge





8. Package Dimensions

PDFN 3.3x3.3-8L (Dual) Package



Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	0.70	0.90
b	0.25	0.39
c	0.14	0.20
D	3.10	3.50
D1	3.05	3.25
D2	0.90	1.20
e	0.55	0.75
E	3.10	3.50
E1	2.90	3.10
E2	1.60	1.90
H	0.27	0.57
K	0.45	-
L	0.30	0.60
L1	0.05	0.25
L2	-	0.15
M	0.23	-
θ	8°	12°