


**30mA Surface Mount Schottky Barrier Rectifiers-40V****PRIMARY CHARACTERISTICS**

V_{RM}	40V
I_O	30mA
V_F	0.37V
$T_{J,Max}$	125°C

**SCHEMATIC DIAGRAM
SOD-323 PACKAGE**

Marking Code: 5 or C9 or E4 or 5E

Ex :

**FEATURES**

- Small Surface Mounting Type
- Low Reverse Current and Low Forward Voltage
- High Reliability
- High Speed Switching
- Moisture Sensitivity Level 1

MECHANICAL DATA

- Case : Molded plastic, SOD-323
- Polarity : Shown above
- Terminals : Plated terminals, solderable per MIL-STD-750, Method 2026
- Epoxy : UL94-V0 rated flame retardant

Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RM}	40	V
Reverse Voltage	V_R	30	V
Mean Rectifying Current	I_O	30	mA
Peak Forward Surge Current (60 Hz for 1 Cyc.)	I_{FSM}	200	mA
Junction Temperature	T_j	125	°C
Storage Temperature Range	T_{stg}	- 40 to + 125	°C

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Typ.	Max.	Unit
Forward Voltage at $I_F = 1\text{ mA}$	V_F	-	0.37	V
Reverse Current at $V_R = 30\text{ V}$	I_R	-	0.5	μA
Capacitance Between Terminals at $V_R = 1\text{ V}$, $f = 1\text{ MHz}$	C_T	2	-	pF




Fig. 1 Forward characteristics






Fig. 3 Capacitance between terminals characteristics

Outline Drawing

SOD-323



Dimensions in inches and (millimeters)

Rev.E




Suggested Soldering Pad Layout	SOD-323
Dimensions in inches and (millimeters)	
RevA	



30mA Surface Mount Schottky Barrier Rectifiers-40V

SOD-323 Embossed Carrier Tape




Packaging Description:


SOD-323 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOD-323	1.48	3.3	1.25	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOD-323 Tape Leader and Trailer



SOD-323 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

**Ordering Information:**

Device PN	Marking ⁽⁴⁾	Packing
SCS751V-T ⁽¹⁾ H ⁽²⁾ -WS ⁽³⁾	5/C9/E4/5E	Tape&Reel: 3 Kpcs/Reel

Note: (1) Packing code, Tape & Reel Packing

(2) Packing code Suffix"H" for halogen free product. All materials and products supplied comply with the U.S. Toxic Substances Control Act statement, PBT Chemicals.

(3) Willas brand abbreviation, Label Type does not display.

(4) There may be additional marking, which relates to the lot trace code information (data code and vendor code), the logo or the environmental category on the device.

*****Disclaimer*****

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

This is the preliminary specification. WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.

◆Mounting and Storage Conditions

Willas has set the following requirements for the heat resistance of components.


[Assumption] Moisture absorption prior to the reflow/flow soldering of components in dry pack.

With components in dry pack, reflow/flow soldering shall be completed within 168 hours after unpacking

(Storage environment:30°C 70%RH)

1.Reflow soldering

Temperature profile



Conditions

	Components size ^{*1}	☐ 28mm or less	☐ Over 28mm	Unit
A	Temp. rise gradient ^{*2}	1 - 3		°C/sec
B	Heating time	50 - 150		sec
	Heating temperature	120 - 180		°C
C	Temp. rise gradient ^{*2}	1 - 3		°C/sec
D	Time over 230°C	90	70	sec
	Peak temperature	260	250	°C
	Peak-temp. hold time	1-10	1-10	sec
Soldering		2		times

*1.Length or width, whichever is the greater outside dimension (length for a rectangular component)

*2.Temperatures and time for A through E in the table above shall be measured on the top surface of the components size.


*3.Time over 217 °C be 90-150 seconds .

2.Flow (wave) soldering (solder dipping)

Peak temperature	260°C
Dipping time	10 sec
Soldering	1 time

SMD : Dipping the entire component

component for Insertion :Dipping to the lead joint of component



3. Hand soldering / touchup

Soldering iron tip temperature	380°C
Soldering time	3 sec



威倫電子股份有限公司

WILLAS ELECTRONIC CORP

Moisture Sensitivity Level (MSL)

If devices are not handled correctly, in accordance with their MSL conditions, then they will start to naturally absorb moisture. When heated rapidly during reflow soldering, the moisture turns to steam. If it cannot escape quickly enough the pressure built up may damage the component by cracking the package moulding, an effect known as “Popcorning”.

IPC/JEDEC J-STD-020C also defines device MSLs as part of the specification. MSL Level 1 is used for products supplied without moisture proof packaging. The products of Willas have an MSL Level of 1.

The Table below details the MSL Levels and conditions defined by J-STD-020C

MSL	Floor Life Time	Floor Conditions
1	Unlimited	$\leq 30^{\circ}\text{C}/ 85\% \text{ RH}$
2	1 Year	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$
2a	4 Weeks	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$
3	168 Hours	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$
4	72 Hours	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$
5	48 Hours	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$
5a	24 Hours	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$
6	Time on Label	$\leq 30^{\circ}\text{C}/ 60\% \text{ RH}$