

**90W Surface Mount TVS For ESD Protection****FEATURES**

- Ultra low capacitance: 0.3pF typical
- Ultra low leakage : nA level
- Operating voltage : 15V
- Low clamping voltage
- 2-pin leadless package

APPLICATIONS


- Cellular Handsets and Accessories
- Serial ATA
- MDDI Ports
- USB Ports
- PCI Express and Serial SATA Ports

MECHANICAL DATA

- Case : Molded, plastic DFN1006-2L
- Polarity : Shown follows
- Epoxy : UL94-V0 rated flame retardant

IEC COMPATIBILITY

- IEC 61000-4-2 (ESD) $\pm 20\text{kV}$ (air), $\pm 15\text{kV}$ (contact)
- IEC 61000-4-5 (Lightning) 2.5A (8/20 μs)

DFN1006-2L PACKAGE**SCHEMATIC & PIN CONFIGURATION**

**Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)**


Parameter	Symbol	Value	Unit
Peak Pulse Power(8/20 μs)	Ppk	90	W
Peak Pulse Current(8/20 μs)	I _{PP}	2.5	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V _{ESD}	± 20 ± 15	kV
Operating Temperature Range	T _J	-55 to +125	$^{\circ}\text{C}$
Storage Temperature Range	T _{stg}	-55 to +150	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V _{RWM}			15	V	
Breakdown Voltage	V _{BR}	16.7			V	I _T = 1mA
Reverse Leakage Current	I _R			0.2	μA	V _{RWM} = 15V
Clamping Voltage	V _C			26	V	I _{PP} = 1A (8 x 20 μs pulse)
Clamping Voltage	V _C			35	V	I _{PP} = 2.5A (8 x 20 μs pulse)
Junction Capacitance	C _J		0.3	0.5	pF	V _R = 0V, f = 1MHz




Typical Performance Characteristics (TA=25°C unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power Derating Curve



8 X 20 s Pulse Waveform



Note: Data is taken with a 10x attenuator


ESD Clamping Voltage

8 kV Contact per IEC61000-4-2




Outline Drawing

DFN1006-2L



Dimensions in inches and (millimeters)

Rev.B-1



**Ordering Information:**

Device PN	Marking ⁽⁴⁾	Packing
SESD15LCDBD -T ⁽¹⁾ H ⁽²⁾ -WS ⁽³⁾	R15	Tape&Reel: 10 Kpcs/Reel

Note: (1) Packing code, Tape & Reel Packing

(2) Packing code suffix "G" for RoHS product : Packing code Suffix "H" for halogen free product.
All materials and products supplied comply with the U.S. Toxic Substances Control Act statement, PBT Chemicals.

(3) Willas brand abbreviation, Label Type does not display

(4) There may be additional marking, which relates to the lot trace code information (data code and vendor code), the logo or the environmental category on the device

*****Disclaimer*****

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

This is the preliminary specification. WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.