

PRIMARY CHARACTERISTICS

I_{FSM}	100 A
I_F	5A X 2
V_{RRM}	40~200V
V_F	0.55V,0.70V,0.85V,0.92V
T_J Max	125°C,150°C

FEATURES

- Guard Ring for over voltage Protection
- High forward surge capability
- High frequency operation
- Component in accordance to RoHS 2002/95/EC
- Moisture Sensitivity Level 1

ITO-220 PACKAGE

- Body Marking Example [X:Please see specifications](#)



(Samples are usually not indicated Date Code)

V:Product Lines

Y:AD late code, ex : 3-2013,4-2014

M:Month, ex : 1-1,2-2,---10-O,11-N,12-D

MECHANICAL DATA

- Case: Molded plastic, ITO-220
- Polarity: Shown above
- Terminals :Plated terminals, solderable per MIL-STD-750,Method 2026
- Epoxy : UL94-V0 rated flame retardant

MAXIMUM RATINGS (TA=25°C unless otherwise noted)

PARAMETER	SYMBOL	SP1040C	SP1060C	SP10100C	SP10150C	SP10200C	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	40	60	100	150	200	V
Maximum RMS voltage	V _{RMS}	28	42	70	105	140	V
Maximum DC blocking voltage	V _{DC}	40	60	100	150	200	V
Maximum average forward rectified current (Total) (Per Leg)	I _F	10 5					A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	100.0					A
Maximum Instantaneous Forward Voltage IF=5A @ 25°C	V _F	0.55	0.70	0.85	0.92		V
Maximum DC Reverse Current @ Tc=25°C at Rated DC Blocking Voltage @ Tc=125°C	I _R	0.5 20		0.2 5			mA
Typical Junction Capacitance(NOTE1)	C _j	250	200	150			pF
Typical Thermal Resistance	R _{θJC}	3					°C/W
Operating Temperature Range	T _J	-55 to +125			-55 to +150		°C
Storage Temperature Range	T _{STG}	-55 to +150					°C

NOTES:1.Measured at 1.0MHZ and applied reverse voltage of 4.0V DC

FIG. 1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2-TYPICAL FORWARD CHARACTERISTICS




FIG. 3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4-TYPICAL REVERSE CHARACTERISTICS






FIG. 5-TYPICAL JUNCTION CAPACITANCE



Outline Drawing

ITO-220



Dimensions in inches and (millimeters)

Rev.J

Ordering Information:

Device PN	Packing
Part Number - ⁽¹⁾ G ⁽²⁾ -WS	Tube Packing:50pcs/Tube; 1000pcs/Box

Note: 1. Packing code: Empty is Tube Packing

2. RoHS product for packing code suffix "G", Halogen free product for packing code suffix "H" .

*****Disclaimer*****

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

This is the preliminary specification. WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.